

# NEW UTILITY PATENT APPLICATION TRANSMITTAL (Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.  
SAR 13070

Total Pages in this Submission

## TO THE ASSISTANT COMMISSIONER FOR PATENTS

Box Patent Application  
Washington, D.C. 20231

EI418926538US

Transmitted herewith for filing under 35 U.S.C. 111(a) and 37 C.F.R. 1.53(b) is a new utility patent application for an invention entitled:

**SECURE INFORMATION DISTRIBUTION SYSTEM UTILIZING INFORMATION SEGMENT SCRAMBLING**

and invented by:

**Glenn A. Reitmeier, Michael Tinker**

If a **CONTINUATION APPLICATION**, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: \_\_\_\_\_

Enclosed are:

### Application Elements

1. ☒ Filing fee as calculated and transmitted as described below
2. ☒ Specification having 25 pages and including the following:
  - a. ☒ Descriptive Title of the Invention
  - b. ☐ Cross References to Related Applications (if applicable)
  - c. ☐ Statement Regarding Federally-sponsored Research/Development (if applicable)
  - d. ☐ Reference to Microfiche Appendix (if applicable)
  - e. ☒ Background of the Invention
  - f. ☒ Brief Summary of the Invention
  - g. ☒ Brief Description of the Drawings (if drawings filed)
  - h. ☒ Detailed Description
  - i. ☒ Claim(s) as Classified Below
  - j. ☒ Abstract of the Disclosure
3. ☒ Drawing(s) (when necessary as prescribed by 35 USC 113)
  - a. ☐ Formal
  - b. ☒ Informal

Number of Sheets 5

**NEW UTILITY PATENT APPLICATION TRANSMITTAL  
(Large Entity)**

*(Only for new nonprovisional applications under 37 CFR 1.53(b))*

Docket No.  
SAR 13070

Total Pages in this Submission

**Application Elements (Continued)**

4. ☒ Oath or Declaration
- a. ☒ Newly executed (*original or copy*)      ☐ Unexecuted
- b. ☐ Copy from a prior application (37 CFR 1.63(d)) (*for continuation/divisional application only*)
- c. ☒ With Power of Attorney      ☐ Without Power of Attorney
5. ☐ Incorporation By Reference (*usable if Box 4b is checked*)  
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.
6. ☐ Computer Program in Microfiche (*Appendix*)
7. ☐ Nucleotide and/or Amino Acid Sequence Submission (*if applicable, all must be included*)
- a. ☐ Paper Copy
- b. ☐ Computer Readable Copy (*identical to computer copy*)
- c. ☐ Statement Verifying Identical Paper and Computer Readable Copy

**Accompanying Application Parts**

8. ☐ Assignment Papers (*cover sheet & document(s)*)
9. ☐ 37 CFR 3.73(B) Statement (*when there is an assignee*)
10. ☐ English Translation Document (*if applicable*)
11. ☐ Information Disclosure Statement/PTO-1449      ☐ Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Acknowledgment postcard
14. ☒ Certificate of Mailing
- ☐ First Class      ☒ Express Mail (*Specify Label No.:*) EI418926538US
15. ☐ Certified Copy of Priority Document(s) (*if foreign priority is claimed*)

**NEW UTILITY PATENT APPLICATION TRANSMITTAL  
(Large Entity)**

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.  
SAR 13070

Total Pages in this Submission

**Accompanying Application Parts (Continued)**

16. ☐ Additional Enclosures (please identify below):


**Fee Calculation and Transmittal**

**CLAIMS AS FILED**

For	#Filed	#Allowed	#Extra	Rate	Fee
Total Claims	29	- 20 =	9	x \$22.00	\$198.00
Indep. Claims	5	- 3 =	2	x \$82.00	\$164.00
Multiple Dependent Claims (check if applicable) <input type="checkbox"/>					\$0.00
BASIC FEE					\$790.00
OTHER FEE (specify purpose) _____					
TOTAL FILING FEE					\$1,152.00

- ☐ A check in the amount of \_\_\_\_\_ to cover the filing fee is enclosed.
- ☒ The Commissioner is hereby authorized to charge and credit Deposit Account No. **04-0203** as described below. A duplicate copy of this sheet is enclosed.
- ☒ Charge the amount of **\$1,152.00** as filing fee.
  - ☒ Credit any overpayment.
  - ☒ Charge any additional filing fees required under 37 C.F.R. 1.16 and 1.17.
  - ☐ Charge the issue fee set in 37 C.F.R. 1.18 at the mailing of the Notice of Allowance, pursuant to 37 C.F.R. 1.311(b).

Dated: **30 October 1998**

  
\_\_\_\_\_  
Signature  
**John V. Silverio**  
Attorney for Applicant's  
Registration No. 34,014

cc:

## **Secure Information Distribution System Utilizing Information Segment Scrambling**

This application claims the benefit of U.S. Provisional Application  
5 No. 60/097,264, filed August 20, 1998, which is herein incorporated by  
reference in its entirety.

The invention relates to information distribution systems and, more  
particularly, the invention relates to methods and apparatus for securing  
10 information distributed within an information distribution system.

### **BACKGROUND OF THE DISCLOSURE**

In several communications systems the data to be transmitted is  
compressed so that the available bandwidth is used more efficiently. For  
15 example, the Moving Pictures Experts Group (MPEG) has promulgated  
several standards relating to digital data delivery systems. The first,  
known as MPEG-1 refers to ISO/IEC standards 11172 and is incorporated  
herein by reference. The second, known as MPEG-2, refers to ISO/IEC  
standards 13818 and is incorporated herein by reference. A compressed  
20 digital video system is described in the Advanced Television Systems  
Committee (ATSC) digital television standard document A/53, and is  
incorporated herein by reference.

The above-referenced standards describe data processing and  
manipulation techniques that are well suited to the compression and  
25 delivery of video, audio and other information using fixed or variable  
length digital communications systems. In particular, the  
above-referenced standards, and other "MPEG-like" standards and  
techniques, compress, illustratively, video information using intra-frame  
coding techniques (such as run-length coding, Huffman coding and the  
30 like) and inter-frame coding techniques (such as forward and backward  
predictive coding, motion compensation and the like). Specifically, in the  
case of video processing systems, MPEG and MPEG-like video processing  
systems are characterized by prediction-based compression encoding of

860E07 "EE628T60

video frames with or without intra- and/or inter-frame motion compensation encoding.

Present electronic distribution systems typically do not strike an appropriate balance between flexibility and security for the purposes of some information distribution applications. For example, to enable the electronic distribution of motion pictures (i.e., film) and other entertainment video applications, it is necessary to dynamically process "trailers" (i.e., short previews of coming attractions") on a location by location basis, in addition to full length motion pictures. With respect to security, it is obviously necessary to incorporate a high level of security, ideally using a multi-layer security approach, such that the valuable intellectual property transmitted within the system is not compromised.

Therefore, a need exists in the art for a secure and flexible method and apparatus for distributing information such as high-value motion pictures and other audio-video information, as well as other forms of data. Additionally, it is seen to be desirable to provide enhanced security for various media, such as digital versatile disk (DVD) and other media.

### SUMMARY OF THE INVENTION

A method and apparatus for securing and, optionally, distributing an information stream by divided the information stream into a collection of segments and compressing the segments, rearranging the order of the segments and encrypting the segments prior to, e.g., distributing the encrypted segments to one or more users within an information distribution system.

Specifically, in one embodiment of the invention, an input information stream is divided into a collection of information segments, the individual segments are then compressed and arranged in a non-standard (i.e., scrambled) manner to produce a scrambled collection of information segments and an associated index table suitable for use in rearranging the collection of information segments into a standard (i.e., unscrambled) order. The scrambled collection of information segments and the associated index table are encrypted (using the same or different encryption techniques) and distributed to one or more subscribers (using

the same or different distribution channels). Optionally, the scrambled collection of information segments is distributed using a plurality of distribution channels (i.e., multipath distribution) and/or at a plurality of different times (i.e., temporally staggered distribution).

5

### BRIEF DESCRIPTION OF THE DRAWING

The teachings of the present invention can be readily understood by considering the following detailed description in conjunction with the accompanying drawings, in which:

10        FIG. 1 depicts an information distribution system 100 including apparatus according to the invention;

          FIG. 2 depicts a graphic representation of collection of information segments arranged in a non-standard (i.e., scrambled) order, and an index table suitable for use in rearranging the collection of information  
15 segments into a standard (i.e., unscrambled) order;

          FIG. 3 depicts a flow routine of an information provider processing method according to the invention;

          FIG. 4 depicts a flow diagram of a subscriber side method for processing an information stream according to the invention; and

20        FIG. 5 depicts a diagrammatic representation of the a layered security environment enabled by the invention.

To facilitate understanding, identical reference numerals have been used, where possible, to designate identical elements that are common to the figures.

25

### DETAILED DESCRIPTION

The invention will be described within the context of an MPEG-like information distribution system. It will be recognized by those skilled in the art that the invention is applicable to many types of information  
30 distribution systems. More specifically, the invention is ideally suited to the protection and dissemination of information streams comprising related sequenced of video and/or audio information, such as motion pictures, television and the like.

FIG. 1 depicts an information distribution system 100 including apparatus according to the invention. Specifically, FIG. 1 depicts an information distribution system 100 comprising information provider equipment (105-140), information distribution channels (145A and 145B), and subscriber equipment (150-175). The information distribution system 100 receives an input information stream IN', illustratively an audio-visual information stream such as a motion picture video stream and one or more associated audio or data streams. The input information stream IN' is processed by the provider equipment to produce a secure information stream that is coupled to the subscriber equipment via the information distribution channel(s). The secure information stream is received and processed by the subscriber equipment to produce an output information stream OUT' comprising the initial audio-visual information stream IN'.

In one embodiment of the invention, a movie or other program is compressed as a collection of self-contained MPEG-2 sequences, which may be of non-uniform duration and size (number of bits). For distribution/storage, the sequences may be arbitrarily re-ordered and an index table built that contains pointers to the storage locations of sequences ordered in their correct presentation sequence. The reordered sequences may be encrypted using standard encryption techniques. The index table may be separately encrypted using the same or different encryption techniques. In addition, the index table may be distributed using a different medium. For example, the encrypted and re-ordered sequences may be distributed on a DVD-ROM, while the encrypted index table is downloaded to the receiver/decoder from an on-line server. Alternatively, a smart card could be used for the index table. Many variations are possible. At the receiver, the decrypted index table is used to control the random access readout of the encrypted sequences from the storage medium. The video sequences are decrypted, decompressed and displayed in their proper order.

The index table approach not only achieves scrambling, but it also provides an approach to flexibly accommodate trailers. The re-ordered video storage distributed to all locations would contain all trailers. The

2025 RELEASE UNDER E.O. 14176

index table distributed to a particular location may indicate the desired subset of trailers. In this manner, the index table and reordering approach provides both multi-level security and trailer-handling flexibility.

- 5           It should be noted that within the scope of this invention, video and audio may be separately segmented and independently re-ordered, with separate index tables for each. Similarly, separate video components (e.g., R, G and B) may also be treated separately.

10           The information provider equipment within the information distribution system 100 of FIG. 1 comprises an optional pixel domain encoder module 105, a segmentation module 110, a compression module 115, a re-sequencing module 130, an information stream encryption module 135, an index table encryption module 140, and a plurality of optional provider storage modules 122, 124 and 126.

- 15           The optional pixel domain encoder 105 receives and processes the input information stream IN' according to one or more of a plurality of pixel domain (or audio domain) processing techniques. These techniques will be described in more detail below with respect to FIG. 3. As an example, the optional pixel domain encoder 105 may impart a digital watermarking to video information within the received input information stream IN' such that copyright notices, source designation and other information related to, e.g., the allowable use and/or ownership of the input information stream IN' may be inserted. The pixel domain encoder 105 produces a pixel (or audio) domain encoded information stream IN
- 20           that is coupled to the segmentation module 110. It should be noted that within the context of this disclosure, the term "pixel domain" is used to denote more than the pixel or baseband video or image information. The term "pixel domain" is used to additionally denote audio and other information (i.e., data) associated with the pixel or baseband video or image information of the underlying information stream being processed.
- 25           30

          The segmentation module 110 divides the encoded (or unencoded) information stream IN into a plurality of segments to produce a segmented information stream. The segmented information stream is then coupled to compression 115A and, optionally, stored in a first

360E01" E628T60





example, in the case of the input information stream in comprising a video information stream and associated audio information stream (e.g., a motion picture), compression module 115A may be used to encode the video information according to an MPEG-2 compression technique, and  
5 the audio information according to an AC-3 or other audio encoding technique. Compression module 115A produces a compressed information stream that is coupled to re-sequencing module 130 and, optionally, stored in a second provider storage module 124.

It should be noted that the order of segmentation module 110A and  
10 the compression module 115A may be reversed. Thus, in FIG. 1, an alternate processing path for the input information stream IN is provided in which a compression module 115B is used to process the input information stream IN prior to segmentation by a segmentation module 110B.

15 Re-sequencing module 130 rearranges the compressed information segments according to a predetermined or pseudo-random pattern. That is, re-sequencing module 130 "shuffles" the compressed and segmented information stream to produce a reordered or re-sequenced compressed and segmented information stream and an associated index table  
20 indicative of the re-sequencing operation performed upon the compressed and segmented information stream. The re-sequencing module 130 re-sequences the underlying video and/or audio information according to one or more of several criteria, such as scene boundaries, GOP size, temporal or frame displacements, frame count, and the like. The  
25 re-sequenced compressed and segmented information stream is coupled to the information stream encryption module 135, while the associated index table is coupled to the index table encryption module 140. Optionally, the output of re-sequencing module 130 is coupled to third local storage module 126.

30 It is critical to the understanding of the present invention to note that the purpose of the segmentation module 110A and the re-sequencing module 115A is to rearrange, in a seemingly random manner, e.g., the video and/or audio information associated with an underlying audio-video information stream such that the presentation continuity of the

0948293-103098

underlying audio-video information is destroyed. That is, the segmentation module 110A and the re-sequencing module 115A remove the temporal continuity of the underlying audio video information in a manner that renders the audio-video information unusable, or at least  
5 unenjoyable, to a pirate or unauthorized subscriber.

The information stream encryption module 135 scrambles the re-sequenced compressed and segmented information stream using one or more known scrambling techniques. Additionally, the index table produced by re-sequencing module 130 is coupled to another encryption  
10 module 140, where it is encrypted in one of a number of known manners to produce an encrypted index table. The encrypted information stream (i.e., the scrambled re-sequenced, compressed and segmented information stream) and the encrypted index table are coupled to information consumer or subscriber side equipment via, e.g., distribution network 145  
15 and/or alternate distribution network 145A.

The optional first 122, second 124 and third 126 local storage module 126 are used to store, respectively, the output of segmentation module 110A (or compression module 115B), the output of compression module 115A (or segmentation module 110B) and the output of re-sequencing module 130.  
20 The local storage modules may be used to, e.g., store such information for further processing by additional processing devices (not shown) or to allow processing of an entire information stream at each step (e.g., perform all segmentation of a received input information stream IN, then perform all compression of the segmented information stream, then perform all  
25 re-sequencing of the compressed and segmented information stream, etc.). Optionally, the server side equipment may be used as a temporary buffer during a "one pass" processing of an input information stream IN (such as a live broadcast of a baseball game).

Distribution network 145A and alternate distribution network 145B  
30 may comprise any one of a number of standard distribution networks such as, microwave links, fiber optic networks, satellite links, cable television links, DVD, Internet, broadcast and the like.

In one embodiment of the invention an alternate distribution network 145B is utilized to transport some of all of the scrambled

0918293103098  
060607"EE62BT60

sequences produced by encryption module 135. That is, the alternate distribution network 145B may be used to transport, e.g., every fifth or some other portion of the scrambled sequences produced by the encryption module 135. In this manner, an unauthorized user intercepting the  
5 information carried by distribution network 145A would, even in the case of breaking the various encrypt codes and properly re-sequencing the scrambled segments, be unable to retrieve all of the scrambled sequences. Thus, alternate distribution network 145B provides an additional layer of security within the information distribution system 100 if FIG. 1.

10 The subscriber side equipment within the information distribution system 100 of FIG. 1 comprises a local storage module 155, a decryption module 150, a second decryption module 160, a random access module 165, a decompression module 170 and an optional pixel domain decoding module 175.

15 The local storage module 155 receives the scrambled sequences transported by distribution network 145A and/or 145B and stores the scrambled sequences. The first decryption module 150 is used to decrypt the encrypted index table transported by distribution network 145A to produce a decrypted index table. The decrypted index table is coupled to  
20 random access module 165. Second decryption module 160 accesses local storage module 155 to retrieve scrambled sequences that are stored and, responsively, decrypt those scrambled sequences. The decrypted scrambled sequences (i.e., unscrambled sequences) are then coupled to random access module 165. Random access module 165 utilizes the index  
25 table information received from first decryption module 150 to rearrange the descrambled sequences received from decryption module 160 to produce a properly sequenced information stream at an output. That is, the output of random access module 165 comprises an information stream having a plurality of segments that are arranged in a manner providing  
30 continuity within the underlying, illustratively, audio visual information stream. Decompression module 170 receives the information stream produced by random access module 165 comprising correctly arranged information segments and, responsively, decompresses the received information stream to produce one or more output information streams

SECRET E628750

(i.e., an audio information stream, a video information stream and any ancillary data streams). The output information stream OUT is optionally subjected to pixel domain decoding module 175, where a pixel domain decode process that is inverse of the pixel domain encoding process

5 performed by pixel encoder 105 occurs.

FIG. 2 depicts a graphic representation of collection of information segments arranged in a non-standard (i.e., scrambled) order, and an index table suitable for use in rearranging the collection of information segments into a standard (i.e., unscrambled) order. In the graphic  
10 representation of FIG. 2, the collection of information segments are stored in a memory such as local storage unit 155 of the system 100 of FIG. 1, and the index table comprises a list of storage locations from which to read, in order, to reconstruct the original order of the information segments. In this manner, improperly obtained distributed data that is scrambled is not  
15 useful unless the index table is also obtained.

Specifically, FIG. 2 depicts an association between six locations (A-F) and six sequences (sequence 1 - sequence 6). It should be noted that in FIG. 2 an oval indicative of a storage module is shown containing a table associating the locations and sequences. Specifically, location A is  
20 associated with sequence 3, location B is associated with sequence 5, location C is associated with sequence 2, location D is associated with sequence 1, location E is associated with sequence 6 and location F is associated with sequence 4. Thus, an index table comprising the following sequence {D, C, A, F, B, E} indicates that the sequence is stored in memory  
25 should be retrieved, prior to being utilized, according to the associations described above to produce a properly sequenced information stream.

FIG. 3 depicts a flow routine of an information provider processing method according to the invention. The routine 300 depicted in FIG. 3 is directed towards processing an audio video stream to produce a  
30 segmented, encoded, re-sequenced and encrypted audio and video information stream and associated index information suitable for re-sequencing the segments.

The routine 300 is entered at step 302 and proceeds to step 304. At step 304 an optional pixel domain encoding process is performed on the

SECRET-EE528T60

video information within a received audio video information stream. For example, the pixel domain encoding process of step 304 may comprise a watermarking process, a pixel encryption process, a lip sync modification process, an audio suppression process or a chroma stripping process.

- 5 Watermarking involves the insertion of identifying an issue within video portion of an information stream such that copyright and other source indicative information may be included within a distributed information stream. Pixel encryption comprises any one of a number of encryption techniques which render pixel information unusable without the
- 10 corresponding pixel decryption processing. Lip sync modification comprises a change in synchronization of the video and associated audio information based upon a random or predetermined temporal parameter such that video and audio are no longer synchronized, thereby severely degrading the presentation of the audio video information stream. Audio
- 15 suppression comprises techniques for suppressing or otherwise hiding audio information from a downstream audio decoder, such that the audio information may only be retrieved by a decoder cognizant of the new location or encoding technique used to hide the audio information. Chroma stripping comprises a process for removing or hiding
- 20 chrominance information from a downstream video decoder, such that the chrominance information may be retrieved only by decoder cognizant of the location or technique used to hide the chrominance information. The routine 300 then proceeds to step 306.

- At step 306 the audio video information stream is segmented into a
- 25 plurality of contiguous information stream segments. These segments may be determined with respect to scene cut indicia, temporal displacement parameters, frame counts, GOP structure and the like. The segments may be of the same or substantially the same length or the segments may be of variable lengths. Each segment is associated with a
- 30 segment identifier such that the original segment arrangement may be preserved by storing segment identifiers with a stream index table. The routine 300 then proceeds to step 308.

At step 308 the segments are compressed according to, e.g., MPEG-2 video and related audio compression techniques. Since the stream

SECRET E628760

segments produced at step 306 are typically self contained with respect to buffer behavior, the compression processes utilized at step 308 may be performed in parallel. That is, multiple audio visual stream segments may be compressed in parallel using a parallel processing or parallel  
5 encoding technique. Otherwise, a single MPEG or other compression module may be used to process each stream segment in a standard manner to produce a compressed output stream comprising a plurality of compressed stream segments. The routine 300 then proceeds to step 310. At step 310 the compressed stream segments are re-sequenced (i.e.,  
10 "shuffled" ) to produce a re-sequenced compressed audio video information stream and associated index table. The index table includes information relating the re-sequenced segments to the initial sequence of segments such that the re-sequenced information stream segments may be rearranged to produce the initial stream segment order. The routine 300  
15 then proceeds to step 312.

At step 312 each of the re-sequenced information stream segments are encrypted to produce an information stream comprising a plurality of encrypted, re-sequenced information stream segments. The routine 300 then proceeds to step 314, where the index table used to maintain  
20 inter-segment associations is itself encrypted. The routine 300 then proceeds to step 316. At step 316 the encrypted information stream segments and the encrypted index table are distributed via, e.g., an information distribution network. The routine 300 then proceeds to step 318 where it is exited.

25 FIG. 4 depicts a flow diagram of a subscriber side method for processing an information stream according to the invention. Specifically, the routine 400 of FIG. 4 is directed towards processing a received encrypted index table and encrypted information segments to extract a properly sequenced audio visual information stream for  
30 subsequent presentation. The routine 400 is entered at step 402 and proceeds to step 404.

At step 404 an encrypted index table received via a distribution network is decrypted to provide a usable index table. The routine 400 then proceeds to step 406, where a plurality of encrypted information stream

091693-0909

segments are decrypted to produce decrypted information stream segments. It must be noted that the decrypted information stream segments are not in a correct sequence with respect to the underlying audio visual information. That is, the decrypted information segments  
5 are "shuffled" such that presentation of the encrypted information stream segments (after, of course, decompression) would result in an undesirable choppy, temporally discontinuous audio visual presentation. The routine 400 then proceeds to step 408.

At step 408 the decrypted information stream segments are accessed  
10 according to information within the decrypted index table. Specifically, the decrypted index table indicates a correct temporal order or sequence for the decrypted information stream segments. Decrypted information stream segments are retrieved from, e.g., a local storage module in a correct temporal or sequential order as indicated by the decrypted index  
15 table to produce a properly sequenced compressed information stream. The routine 400 then proceeds to step 410, where the properly sequenced compressed information stream is decompressed to produce a decompressed audio visual information stream. For example, the decompression process at step 410 is the inverse of the compression  
20 process used at step 308 of the routine 300 of FIG. 3. The routine 400 then proceeds to step 412.

At step 412 an optional pixel domain decoding process is used to decode any pixel domain encoding imparted to the information stream at step 304 of the routine 300 of FIG. 3. The routine 400 then proceeds to step  
25 414, where it is exited.

The above-described invention simultaneously provides for both flexibility and security of electronically stored video information. The essential observation is that, if compressed in an appropriate manner, video information that is stored on a random access storage device can be  
30 re-sequenced with respect to its presentation flow. In normal operation, compressed video typically cannot be chopped up and stored in segments, because the use of bi-directional motion prediction and the constraints of neither overflowing nor underflowing rate buffers prohibit such operation. However, the MPEG-2 syntax does provide mechanisms to treat portions of

SECRET



the video stream as self-contained entities. These mechanisms include the use of I and P frame GOP structures (e.g., "IPPPPPPI...") or other "closed" GOP structures (e.g., "IBBPBBPI...") and the use of splice point syntax that indicates periodic points at which buffers are filled to a known state. The invention provides an overall system that including both flexibility and security.

It must be noted that if the segments are not self contained (e.g., not a closed GOP data structure), the VBV buffer status at the boundaries would provide information to greatly assist in breaking the scrambling and reassembling of the proper video or audio sequence without the decrypted index.

It is important to note that the invention addresses the security weaknesses associated with continuity indicators, such as audio continuity, VBV buffer status, PTS and DTS information and the like. These continuity indicators are useful to those seeking to break the security of the system and retrieve the "secured" data. By isolating or encapsulating such continuity indicators within a segment, and then encoding the segment, the continuity indicators are not useful in decoding the segment.

FIG. 5 depicts a diagrammatic representation of the a layered security environment enabled by the invention. Specifically, FIG. 5 depicts a series of concentric circles representative of security layers. The various layers of security have been described in detail above with respect to FIGS. 1-4. FIG. 5 is useful in understanding the holistic, yet flexible approach to security that is enabled by the invention.

Specifically, a first layer of security is provided by a pixel domain or other baseband information domain (e.g., audio or data domain) processing layer 510. As previously discussed, the exemplary pixel domain process may comprise, e.g., digital watermarking of video information, insertion of copyright notices and other pixel domain security measures. In the case of an information stream comprising an audio information stream or other information stream, the pixel domain

The security aspects of the pixel domain processing layer 510 are augmented by a stream segmentation processing layer 520. The security aspects of the stream segmentation processing layer 520 are augmented by a stream segment scrambling or re-sequencing layer 530. The security aspects of the stream segment scrambling or re-sequencing layer 530 are augmented by an encryption layer 540, including an optional index encryption layer 535.

The second of the additional optional layers comprises a temporal staggering layer 560, in which portions of the information stream processed according to one or more of processing steps 510 through 540 is transmitted to one or more information consumers in a temporarily noncontiguous manner. That is, contiguous information stream segments are transmitted at different times (i.e., in temporally noncontiguous manner) and temporally reassembled by the information consumer(s).

In the case of a single transmission channel, the temporal staggering security layer 560 cannot be used for real time distribution of secure information streams due to the inherent nature of temporal staggering (i.e., inherently not real time using a single channel). However, temporal staggering coupled with multipath distribution may be used to distribute real time information streams. For example, if three distinct communication channels are used to distribute encrypted information segments, then each of the three channels may be used to

5 distribute encrypted information segments offset by three segments from the information segment previously transmitted on that channel. From the perspective of a single channel, each of the transmitted information segments is temporally offset from a preceding or following information stream segment by the time normally associated with transmitting the two intervening information stream segments (i.e., the time normally allocated to transmitting the two information stream segments carried by the other two channels is not used by the one channel). Optionally, this dead time may be filled with dummy information or information likely to cause errors or otherwise help thwart an unauthorized user.

10 In one embodiment of the invention, one or more information distribution channels are used to transmit a plurality of segmented information streams. In this embodiment of the invention, the information segments associated with each of the plurality of segmented information streams are interleaved across the one or more information to be transmitted are interleaved among one or more information distribution channels. The segmented information streams may optionally share encryption keys. The interleave method may be fixed or dynamic. In the case of a dynamic interleave method, information suitable for reconstructing the various information streams may be provided within one or more index tables.

20 While the amount of security afforded by an individual security layer is roughly represented by the relative position of the individual security layer, it must be noted that each layer addresses a different security threat. For example, the pixel domain (or, more generally, the baseband information domain) layer is addresses the identification and/or tracing of unauthorized information stream use and/or users. The segment scrambling and encryption layers address the threat of hackers or other unauthorized users gaining access to useful data within a received information stream. The multiple channel transmission and temporal staggering layers address the physical avoidance of information stream reception by unauthorized users. The entire layered approach is directed toward providing selective layers of security, depending upon, e.g., the sensitivity of the information to be distributed. For example,

securing an electronic program guide may be deemed to be unnecessary. However, securing a first run movie distributed to theaters for subsequent presentation is absolutely necessary.

Although various embodiments which incorporate the teachings of  
5 the present invention have been shown and described in detail herein,  
those skilled in the art can readily devise many other varied embodiments  
that still incorporate these teachings.

RECEIVED

What is claimed is:

1. In an information processing system, a method for securing an information stream comprising a sequence of information frames, said  
5 method comprising the steps of:
  - segmenting said information stream into a plurality of information stream segments having a first segment sequence, each of said information stream segments comprising a plurality of information frames;
  - 10 compressing said information frames forming said information stream segments;
    - re-sequencing said information stream segments to produce a re-sequenced information stream having a second segment sequence, said first segment sequence being related to said second segment sequence by  
15 an index; and
    - encrypting said re-sequenced information stream and said index.
2. The method of claim 1, further comprising the steps of:
  - distributing said encrypted re-sequenced information stream and  
20 said index to one or more information consumers.
3. The method of claim 2, wherein, said step of distributing comprises the steps of:
  - distributing, via a first medium, said encrypted re-sequenced  
25 information stream; and
  - distributing, via a second medium, said encrypted index.
4. The method of claim 2, wherein said encrypted and re-sequenced information stream segments are distributed to said one or more  
30 information consumers in a temporally discontinuous manner.
5. The method of claim 3, wherein said encrypted and re-sequenced information stream segments are distributed to said one or more information consumers in a temporally discontinuous manner.

0916293 103098

6. The method of claim 5, wherein:  
said second distribution channel comprises a plurality of  
distribution channels, each of said plurality of distribution channels
- 5 distributing a respective plurality of said encrypted and re-sequenced  
information stream segments.
7. The method of claim 1, wherein:  
each of said information stream segments comprises approximately
- 10 a first number of compressed information frames.
8. The method of claim 7, wherein:  
in the case of an information stream segment including one or  
more predictively encoded compressed information frames, said one or
- 15 more predictively encoded compressed information frames being  
predictively encoded using reference information frames within said  
information segment including said one or more predictively encoded  
compressed information frames.
- 20 9. The method of claim 1, wherein:  
a first compressed information frame within each of said  
information segments comprises a non-predicted information frame.
10. The method of claim 1, wherein:
- 25 said information stream comprises a plurality of image frames and  
associated audio frames; and  
each of said information stream segments includes a respective  
first plurality of image frames and a respective second plurality of audio  
frames, said first plurality of image frames and said second plurality of
- 30 audio frames intended for presentation during substantially the same  
temporal period.

0918293 103093

11. The method of claim 1, wherein said information stream comprises a plurality of image frames and associated audio frames, and wherein said step of segmenting comprises the steps of:

segmenting said information stream into a plurality of image  
5 information stream segments having said first segment sequence, each of said image information stream segments comprising a plurality of image frames;

segmenting said information stream into a plurality of audio  
information stream segments having a third segment sequence, each of  
10 said audio information stream segments comprising a plurality of image frames.

12. The method of claim 11, wherein said step of re-sequencing comprises the steps of:

15 re-sequencing said image information stream segments to produce a re-sequenced image information stream having said second segment sequence, said first segment sequence being related to said second segment sequence by said index; and

re-sequencing said audio information stream segments to produce a  
20 re-sequenced audio information stream having said fourth segment sequence, said third segment sequence being related to said fourth segment sequence by said index.

13. The method of claim 12, wherein said image information stream  
25 and said audio information stream are encrypted using one of a common encryption technique using a common encryption key, a common encryption technique using different encryption keys, different encryption techniques using a common encryption key and different encryption techniques using different encryption keys.

30

14. The method of claim 1, wherein  
said step of compressing said information frames produces control  
information indicative of a utilization level of a decoder buffer; and

09482931-103098

said step of encrypting includes a step of encrypting said indicia of decoder buffer utilization.

15. In an information processing system, a method for recovering  
5 information frames from an information stream formed according to the  
securing method of claim 1, said method for recovering comprising the  
steps of:
- recovering said index relating said second segment sequence to said  
first segment sequence;
  - 10 decrypting said encrypted information stream segments to produce  
corresponding decrypted information stream segments;
  - re-sequencing, using said recovered index, said decrypted  
information stream segments; and
  - decompressing, using a decompression process associated with  
15 said compression process, said compressed information frames included  
within said decrypted information stream segments.
16. The method of claim 15, wherein:
- said encrypted re-sequenced information stream is received via a  
20 first medium; and
  - said encrypted index is received via a second medium.
17. The method of claim 16, wherein said encrypted and re-sequenced  
information stream segments are received in a temporally discontinuous  
25 manner.
18. The method of claim 15, wherein said step of re-sequencing  
comprises the steps of:
- accessing, from a random access storage containing at least some  
30 of said decrypted information stream segments, said decrypted  
information stream segments according to said first segment sequence.
19. In an information processing system, a method for recovering  
information frames from an information stream formed according to the

09182933 103098



securing method of claim 1, said method for recovering comprising the steps of:

recovering said index relating said second segment sequence to said first segment sequence;

5 re-sequencing, using said recovered index, said encrypted information stream segments;

decrypting said encrypted information stream segments to produce corresponding decrypted information stream segments; and

10 decompressing, using a decompression process associated with said compression process, said compressed information frames included within said decrypted information stream segments.

20. The method of claim 19, wherein:

15 said encrypted re-sequenced information stream is received via a first medium; and

said encrypted index is received via a second medium.

21. The method of claim 20, wherein said encrypted and re-sequenced information stream segments are received in a temporally discontinuous  
20 manner.

22. The method of claim 19, wherein said step of re-sequencing comprises the steps of:

25 accessing, from a random access storage containing at least some of said encrypted information stream segments, said encrypted information stream segments according to said first segment sequence.

23. In an information distribution system, a method for recovering an information stream having a first segment sequence from an encrypted  
30 re-sequenced information stream having a second segment sequence, said method comprising the steps of:

recovering an index relating said second segment sequence to said first segment sequence;

SECRET "EE629T60

decrypting said encrypted information segments to form respective decrypted information segments;

- re-sequencing, using said recovered index, said decrypted information segments to form an information stream comprising a plurality of information segments arranged according to said first segment sequence; and

decompressing a plurality of information frames forming each of said information stream segments.

24. In an information processing system, apparatus comprising:  
a segmentation module, for segmenting an information stream into a plurality of information stream segments, said information stream segments arranged according to a first segment sequence, each of said information stream segments comprising a plurality of information frames;

a compression module, for compressing said information frames forming said information stream segments;

- a re-sequencing module, for re-arranging according to a second segment sequence, said information stream segments including said compressed information frames, said first segment sequence being related to said second segment sequence by an index; and

an encryption module, for encrypting said re-sequenced information stream segments and said index

25. The apparatus of claim 23, wherein:  
said index and said encrypted and re-sequenced information stream segments are coupled to one or more information consumers via a distribution channel.

26. The apparatus of claim 23, wherein:  
said index is distributed to one or more information consumers via a first distribution channel; and

0918293103090

said encrypted and re-sequenced information stream segments are distributed to said one or more information consumers via a second distribution channel.

5 27. The apparatus of claim 25, wherein:

said encrypted and re-sequenced information stream segments are distributed to said one or more information consumers in a temporally discontinuous manner.

10 28. The apparatus of claim 26, wherein:

said encrypted and re-sequenced information stream segments are distributed to said one or more information consumers in a temporally discontinuous manner.

15 29. The apparatus of claim 28, wherein:

said second distribution channel comprises a plurality of distribution channels, each of said plurality of distribution channels distributing a respective plurality of said encrypted and re-sequenced information stream segments.


20

0918293-103093  
SECRET

Abstract of the Invention

A method and apparatus for securing and, optionally, distributing an information stream by divided the information stream into a collection  
5 of segments and compressing the segments, rearranging the order of the segments and encrypting the segments.

SECRET






FIG. 2

001223 103093  
060607 0628160




FIG. 3




FIG. 4



SECURITY MODEL




FIG. 5

**COMBINED DECLARATION AND POWER OF ATTORNEY**

As a below-named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first, and sole inventor (if only one name is listed below) or an original, first, and joint inventor (if multiple names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled **SECURE INFORMATION DISTRIBUTION SYSTEM UTILIZING INFORMATION SEGMENT SCRAMBLING**, the specification of which is being filed under the above-identified Attorney Docket Number.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, § 1.56(a).

**PRIORITY CLAIM**

I hereby claim foreign priority benefits under Title 35, United States Code, § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed.

_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	____ Yes ____ No (Priority Claimed)
_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	____ Yes ____ No (Priority Claimed)

I hereby claim the benefit under Title 35, United States Code § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application.

_____ (Application Serial No.)	_____ (Filing Date)	_____ (Status) (patented, pending, abandoned)
_____ (Application Serial No.)	_____ (Filing Date)	_____ (Status) (patented, pending, abandoned)

I hereby claim the benefit under Title 35, United States Code, § 119(e) of any United States provisional application(s) listed below:

**PROVISIONAL APPLICATION NUMBER**  
60/097,264

**FILING DATE**  
20 August 1998

**POWER OF ATTORNEY**

As a named inventor, I hereby appoint the following attorneys jointly and each of them severally, with full power of substitution, delegation, and revocation, to prosecute this application, to make alterations and amendments therein, to receive the patent, and to transact all business in the Patent and Trademark Office connected therewith:

William J. Burke, Reg. No. 29,138  
 John V. Silverio, Reg. No. 34,014  
 Abhik A. Huq, Reg. No. 40,656

I hereby direct that all correspondence and telephone calls in connection with this application be addressed to:

William J. Burke  
 Sarnoff Corporation  
 c/o Patent Operations  
 CN 5300  
 Princeton, NJ 08543-5300  
 Tel.(609) 734-2560  
 Fax.(609) 734-2673

**DECLARATION**

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

**SIGNATURES**

Full name of **first inventor**: Glenn Arthur Reitmeier

Inventor's signature: \_\_\_\_\_

Date: Oct 30, 1998 Country of Citizenship: US

Residence and Post Office Address: 193 Cinnabar Lane, Yardley, PA 19067

Full name of **second inventor**: Michael Tinker

Inventor's signature: \_\_\_\_\_

Date: \_\_\_\_\_ Country of Citizenship: US

Residence and Post Office Address: 35 Highland Drive, Yardley, PA 19067

SECRET "EE628T60"